

38201*Ultimate instep protection. Dual density comfort.***TECHNOLOGIES****■ SHOCK ABSORBER**

Programmed deformation ovoidal vault system. It redirects the load on the cue by distributing it evenly.

■ MICROTEC PRO

Effective antimicrobial protection. Prevents the development of microorganisms and bad odors.

■ DRYMAX

Double layer lining. Textile fabric in contact with the foot and non-woven layer as support. Comfort and durability.

■ RUBBERSKIN

Superficial elastomer seal. It increases chemical and physical resistance.



DESCRIPTION

Model: Welding Ankle Boot

■ UPPER COMPOUND

Color

- Black

Upper

- HQ Full-Grain Leather

Inside

- DRYMAX Lining (bottom part)

Collar

- Non-Padded

Tongue

- None

■ TOE CAP

- Steel

■ ACCESORIES

Laces

- Array

Lace-keepers

Insoles

- Low density rubber comfort insole

■ PLANT

Other properties

- Electrical Hazard
- Resistant to Hydrocarbons
- Slip Resistant
- Self-Cleaning
- Resistant to Flexing
- Resistant to Abrasion
- Grooves for Stair-Climbing
- Wide Tread Base

Compound

- Dual Density Rubber

Upper plant adhesion

- Cemented with bi-component adhesive and sewn with high-endurance threads

■ OPTIONALS

- Steel Shank
- Polypropylene Toe-Cap
- PR - Puncture Resistant

■ SIZES

From 6 to 16

SAFETY HAZARDS SPECIFICATIONS



Last review date: 2022/07/22

WWW.FUNCIONALWEB.COM

The content of this document can be changed without previous notice.

© Maincal 2024