

RANDER GRAY

Ultra-premium 6-inch boots. Perfect fit and comfort. Exclusive design. State-of-the-art technology and components.



TECHNOLOGIES

IPD TECHNOLOGY

Progressive density increase. High comfort, optimum cushioning in the heel area and maximum stability in the step.

ANTITORSION INSERT

Highly dense semi rigid TPU insert. Controls unwanted twisting and protects the arch of the foot.

DURATEX

Fabric with high abrasion and flexion resistance.

AIRCORE

High technology lining, three layer with permanent airflow air chamber.

FOAMFREE

Inside linings without synthetic foam support. It reduces moisture, and increases comfort.

DCP SYSTEM

System of high-density TPU double insert which significantly increases resistance to abrasion and grip.

SHOCK ABSORBER

Programmed deformation ovoidal vault system. It redirects the load on the cue by distributing it evenly.

DRYMAX

Double layer lining. Textile fabric in contact with the foot and non-woven layer as support. Comfort and durability.

MICROTEC PRO

Effective antimicrobial protection. Prevents the development of microorganisms and bad odors.

FUNCIONAL



SUELA P.U.- MULTIDENSIDAD ULTRAPREMIUM RANDER GRAY

DESCRIPTION

Model: 6-inch Boot

UPPER COMPOUND

Color

• Gray

Upper

- Combination of Leather and Textile Fabrics
- Curried Full-Grain Leather

Inside

• DRYMAX Lining (bottom part)

Collar

• Padded

Tongue

• With Bellows, Lined and Padded

TOE CAP

Steel

ACCESORIES

Laces

• Pulling Resistance

Lace-keepers

- High-Endurance Composite, Closed (non-metallic)
- High-endurance composite, open (non-metallic)

Insoles

• Ultra-comfortable, ergonomic, conformed insole

SAFETY HAZARDS SPECIFICATIONS



Last review date: 2022/07/22

PLANT

Other properties

- Electrical Hazard
- Resistant to Hydrocarbons
- Slip Resistant
- Self-Cleaning
- Resistant to Flexing
- Resistant to Abrasion
- Grooves for Stair-Climbing
- Wide Tread Base

Compound

• Multidensity Polyurethane

Upper plant adhesion

• Direct injection

OPTIONALS

- Polypropylene Toe-Cap
- PR Puncture Resistant

SIZES

From 6.5 to 13

WWW.FUNCIONALWEB.COM

The content of this document can be changed without previous notice. © Maincal 2024